

SCHUMAK

LUBRICATING PUMPS

*High Performance
&
High Quality*



SCHUMAK Equipment (India) Pvt. Ltd.

* Grease pumps are available in Air operated and Hand operated models. Air operated pumps are working with air pressure ratio of 50:1. They are mounted on powder coated drums with nylon wheels for easy mobility. Grease guns are made of HF-30 Aluminium forgings.* Hand operated grease pumps also mounted on powder coated drums with wheels.



All the grease pumps are provided with pressure plate for smooth and continuous operation



Oil Drainer
50 Litres



Description	Hand Operated Grease Pump			Air Operated Grease Pump			Air Operated Oil Pump	Hand Operated Oil Pump
	HGP 05	HGP 10	HGP 20	PGP 10	PGP 25	PGP 50	POP 50	HOP 20
Drum Capacity	5 Kgs	10 Kgs	20 Kgs	10 kgs	25 kgs	50 kgs	50 Litres	20 Litres
Out Put	3 Grams / Stroke			350 Grams per minute			14 LPM	0.1 LPM
Air Req.	Nil			325 LPM			325 LPM	NIL
Pressure Req.	Nil			5 to 10kg/cm.sq			5 to 10kg/cm2	NIL
Type of Hose	Double Wire Braided, Oil Resistant and Flexible						Oil Resistant	Oil Resistant
Hose Length	2 Mtrs. Length			2.2 Mtrs. Length			3.5 Mtrs	2.0 Mtrs
Block Pressure	140kg/cm2			425kg/cm2			30kg/cm2	35kg/cm2
Follower Plate	Spring Loaded Type			Dead Weight Type			NIL	NIL

Due to continuous engineering improvements, specifications are Subject to change. The pictures shown in this leaflet are representations ; not the entire range.

SCHUMAK Equipment (India) Pvt. Ltd.,

7/44-1, Kanuvai Industrial Estate, Kanuvai, Coimbatore - 641 108.

Tel. : 0422 - 3253610, 3233483 Fax. : 2659610

Email : schumak@vsnl.net Web site : www.schumakindia.in